



PRODUCT SPECIFICATIONS

Standard Module Size: 8' x 4' (2.44 m x 1.22 m) / 32 sq/ft (2.973 sq/m)
Weight per sq.ft: 2.69 lbs. / 43 oz. / 1.22 kg. / 1219 grams
Weight per sq.m: 28.60 lbs. / 12.97 kg.

Product	Traction Surface	Thickness
DD1	Rugged/ Rugged	½" mat + cleats = 1¼" total
DD2	Pedestrian/ Rugged	½" mat + cleats = 7/8" total
DD3	Pedestrian/ Smooth	½" total
DD4	Smooth/ Rugged	½" mat + cleats = 7/8" total

Module Size:	Module Weight:
8' x 4' (2.44m x 1.22m)	86lbs (39.01kg)
8' x 3' (2.44m x 0.91m)	64.5lbs (29.26kg)
6' x 3' (1.83m x 0.91m)	48.42lbs (21.96kg)
8' x 2' (2.44m x 0.609m)	43lbs (19.5 kg)

- Rugged Traction Surface:** Double-traction tread design includes two parallel traction treads positioned at a 90-degree angle to adjacent double traction tread sets.
- Pedestrian Traction Surface:** Pedestrian friendly alternating cross shaped traction design.
- Smooth Surface:** No traction pattern for easier cleaning and maintenance
- Available Colors:** Black, beige. Custom colors available (minimum order required).
- Material:** Black High-Density Polyethylene (HDPE) post-industrial recycled plastic, naturally UV resistant due to the carbon black used for color. Beige UV-stabilized mats available.
- Weight Loading Capacity:** Varies, depending on sub-surface, up to 80 tons capacity.
- Compressive Strength:** 2,843 psi (ASTM D695-02a)
- Flammability Resistance:** UL-94 HB Rating
- Ground Surface Suitability:** DuraDeck mats are designed to be used with no ground preparation over grass, gravel, soil, concrete, asphalt, mud and sandy soil conditions.
- Connection System:** DuraDeck mats have eight holes: one in each corner and four in the center line (two on each 8ft side) to create multi-directional roadways of nearly any size or shape. Mats can be connected using metal DuraLink connectors. DuraLinks do not require tools to install.
- Shipping:** Pallet maximum is 30 units (4' x 8')
 20' Ocean Container: 250 – 4' x 8' unit order and/or equal to 29,240lbs.
 40' Ocean Container: 500 – 4' x 8' unit order and/or equal to 43,000lbs.
- Warranty:** 7 years against cracking and breaking under normal use.

